

For larger doorset and openable window sizes:

- the height of latch above floor level shall be equal to or greater than the height given in p. 3.10, and such increase in height shall be at least proportional to the increase in door or openable window height;
- the distance of the top hinge from the top of door or openable window leaf shall be equal to or less than given in p. 3.10;
- the distance of the bottom hinge from the bottom of door or openable window leaf shall be equal to or less than given in p. 3.10;
- the distance of the middle hinge from the bottom of door or openable window leaf shall be equal to or greater than given in p. 3.10;
- dimensions of the glass panes and panels shall be proportional to the increase of the door or openable window leaf dimensions.

5.10. Dimensions of the arc-shaped over panel of doorsets or openable windows:

- width: 1725 mm - 2645 mm;
- height: 686 mm - 1052 mm;
- radius: 862 mm - 1357 mm;
- area: 0,881566 m² - 1,880675 m².

5.11. Dimensions of the glass panes in arc-shaped over panel of doorsets or openable windows:

- width: 1560 mm - 2392 mm;
- height: 555 mm - 852 mm;
- radius: 780 mm - 1265 mm;
- area: 0,759595 m² - 1,350392 m².

5.12. Doorsets and openable windows can be fixed to the following supporting constructions:

- masonry thickness of min. 160 mm,
- made of concrete thickness of min. 160 mm,
- made of aerated concrete, thickness of min. 160 mm,
- made of gypsum – plasterboards, thickness of min. 160 mm and fire resistance class not lower than EI 60.